





















Project \_\_\_\_\_  
 AIA # \_\_\_\_\_ SIS # \_\_\_\_\_  
 Item # \_\_\_\_\_ Quantity \_\_\_\_\_ C.S.I. Section 114000



# RACK CAPACITY CHART

For Triple Wide Units – Side & End Load Racks

RACK CAPACITY CHART FOR TRIPLE WIDE UNITS – SIDE & END LOAD RACKS

PW3S Proofer			
Dimensions	SINGLE END LOAD	SINGLE SIDE LOAD	DOUBLE SIDE LOAD
	 Typical Rack Dimensions: 20.38"W x 26.0"D	 Typical Rack Dimensions: 28.38"W x 18.0"D	 Typical Rack Dimensions: 28.38"W x 36.0"D
<b>40.5"D MODELS</b> <b>Interior:</b> 37.8"D x 95.0"W <b>Exterior:</b> 43.3"D x 109.0"W	 <b>4</b>	 <b>6</b>	 <b>3</b>
<b>60.5"D MODELS</b> <b>Interior:</b> 57.8"D x 95.0"W <b>Exterior:</b> 63.3"D x 109.0"W	 <b>8</b>	 <b>8</b>	 <b>3</b>
<b>80.5"D MODELS</b> <b>Interior:</b> 77.8"D x 95.0"W <b>Exterior:</b> 83.3"D x 109.0"W	 <b>11</b>	 <b>12</b>	 <b>6</b>
<b>100.5"D MODELS</b> <b>Interior:</b> 97.8"D x 95.0"W <b>Exterior:</b> 103.3"D x 109.0"W	 <b>12</b>	 <b>15</b>	 <b>6</b>
<b>120.5"D MODELS</b> <b>Interior:</b> 117.8"D x 95.0"W <b>Exterior:</b> 123.3"D x 109.0"W	 <b>16</b>	 <b>18</b>	 <b>9</b>

As continued product improvement is a policy of Baxter, specifications are subject to change without notice.

 CAD and/or Revit Files Available

Approved by \_\_\_\_\_ Date \_\_\_\_\_ Approved by \_\_\_\_\_ Date \_\_\_\_\_